

◆ HT155-01 Operating panel 便携式回收装置

For the Mini Series,

Standard equipment: 包含

1. HT155 Operating panel 操作盘
2. Portable vacuum pump HDV14 真空泵
3. Recovery oil-less Compressor 回收机
4. Rubber hose DN8 管道

Note: Please instruction your power supply information.



◆ HB158 Small SF6 Service Device 小型回收装置

For filling、Recovery & Evacuating to SF6 products. It is suitable for small space such as subway. 适用于地下变电站或者地铁等狭小场所。220V/380V 50/60HZ 可选

Standard equipment:

- Oilfree compressors 5.8NM<sup>3</sup>/h 无油回收机 5.8 NM<sup>3</sup>/h  
Suction pump 3.6NM<sup>3</sup>/h final vacuum 50mbar 回收终压 50mbar  
Vacuum pump (20M<sup>3</sup>/h) final vacuum 0.2mbar 真空终压 0.2mbar  
5 m long rubber hose with DN8 couplings 5米长橡胶管  
Filter unit 过滤器  
Liquid storage into SF6 bottle 灌瓶管

Note: Please instruction your power supply information.



N

1250x750x1580

225kg

---

◆ HB160 SF6 Service Device

For filling 、Recovery & Evacuating to SF6 products.

此设备用于 SF6 气体一般应用的抽真空、充气、回收三大功能。设备采用自主研发的全无油气体压缩机对 SF6 进行压缩并液态储存。压缩机采用非接触式磁力耦合传动方式，实现了无泄漏、过载保护，为开关制造行业及现场服务行业理想的 SF6 处理设备。

Standard equipment:

Oilfree compressors 5.8NM<sup>3</sup>/h 无油回收机 5.8 NM<sup>3</sup>/h

Suction pump 15NM<sup>3</sup>/h final vacuum 1mbar 回收终压 1mbar

Vacuum pump 63M<sup>3</sup>/h final vacuum 0.2mbar 真空终压 0.2mbar

5 m longDN20 rubber hose with couplings 5 米长 DN20 橡胶软管

Filter unit

Computer screen operation

Liquid storage



1860x950x1250

615kg

OPTION:

63 m <sup>3</sup> /h Vacuum pump , Final Vacuum 0.3 mbar	HB160-001
100 m <sup>3</sup> /h Vacuum pump , Final Vacuum 0.3 mbar	HB160-002
40 m <sup>3</sup> /h 2-stage Vacuum pump, Final Vacuum 0.02mbar	HB160-040
60 m <sup>3</sup> /h 2-stage Vacuum pump, Final Vacuum 0.02mbar	HB160-060
300L/50bar tank ,storage capacity 280kg (300L mounted on, attached 300F),	/300L, /300F
600L/50bar tank ,storage capacity 580kg (300L mounted on, attached 600F)	/600L, /600F
1000L/50bar, storage capacity 980kg, only attached	/1000F

Note: Please instruction your power supply information.

◆ HB162 SF6 Service Device

For filling , Recovery & Evacuating to SF6 products.

Standard equipment:

Oilfree compressors 5.8NM<sup>3</sup>/h x2 标配 2 个 5.8 NM<sup>3</sup>/h 压缩机

Suction pump 15NM<sup>3</sup>/h final vacuum 1mbar 回收终压 1mbar

Vacuum pump 63M<sup>3</sup>/h final vacuum 0.2mbar 真空终压 0.2mbar

5 m long DN20 rubber hose with couplings

Filter unit

Computer screen operation

Liquid storage



1860x950x1250

750kg

OPTION:

63 m <sup>3</sup> /h Vacuum pump , Final Vacuum 0.3 mbar	HB162-001
100 m <sup>3</sup> /h Vacuum pump , Final Vacuum 0.3 mbar	HB162-002
40 m <sup>3</sup> /h 2-stage Vacuum pump, Final Vacuum 0.02mbar	HB162-040
60 m <sup>3</sup> /h 2-stage Vacuum pump, Final Vacuum 0.02mbar	HB162-060
300L/50bar tank ,storage capacity 280kg (300L mounted on, attached 300F),	/300L, /300F
600L/50bar tank ,storage capacity 580kg (300L mounted on, attached 600F)	/600L, /600F
1000L/50bar, storage capacity 980kg, only attached	/1000F

Note: Please instruction your power supply information.

◆ HB180 SF6 Service Device

For filling , Recovery & Evacuating to SF6 products.

适用于各类大型 GIS、GIL 等开关的真空、回收、充气。

Standard equipment:

Oilfree compressors 17.2NM<sup>3</sup>/h 无油回收机 17.2 NM<sup>3</sup>/h

Suction pump 15NM<sup>3</sup>/h final vacuum 1mbar 回收终压 1mbar

Vacuum pump 63M<sup>3</sup>/h final vacuum 0.2mbar 真空终压 0.2mbar

5 m long DN20 rubber hose with couplings

Computer screen operation

2100x1400x2180

Filter unit

1400kg

Liquid storage



OPTION:

63 m <sup>3</sup> /h Vacuum pump , Final Vacuum 0.3 mbar	HB180-001
100 m <sup>3</sup> /h Vacuum pump , Final Vacuum 0.3 mbar	HB180-002
40 m <sup>3</sup> /h 2-stage Vacuum pump, Final Vacuum 0.02mbar	HB180-040
60 m <sup>3</sup> /h 2-stage Vacuum pump, Final Vacuum 0.02mbar	HB180-060
Roots pump, vacuum pump 100 m <sup>3</sup> /h, roots 250m <sup>3</sup> /h, Final Vacuum 0.1mbar	HB180-021
Roots pump, vacuum pump 160 m <sup>3</sup> /h, roots 500m <sup>3</sup> /h, Final Vacuum 0.1mbar	HB180-022
Add 1suction pump 15 Nm <sup>3</sup> /h (time-sharin, end pressure is faster )	HB180-200
300L/50bar tank ,storage capacity 280kg (300L mounted on, attached 300F)	/300L, /300F
600L/50bar tank ,storage capacity 580kg (600L mounted on, attached 600F)	/600L, /600F
1000L/50bar, storage capacity 980kg, only attached	/1000F

Note: Please instruction your power supply information.

◆ HBZ 180 SF6 Service Device

For filling , recovery & Evacuating to SF6 products.

适用于开关 GIS\GIL 的生产企业在车间内使用。

Standard equipment:

Oil-free compressors 17.2NM<sup>3</sup>/h 无油回收机 17.2 NM<sup>3</sup>/h

Suction pump 15NM<sup>3</sup>/h final vacuum 1mbar 回收终压 1mbar

Vacuum pump 160M<sup>3</sup>/h Roots pump 500 M<sup>3</sup>/h final vacuum 0.05mbar

5 m long DN20 rubber hose with couplings

Computer screen operation

Filter unit

Liquid storage



2450x1450x1500

1150kg

◆ HB350 SF6 Service Device

For filling , recovery & Evacuating to SF6 products.

适用于开关 GIS\GIL 的生产企业在车间内使用或者是大型 GIS\GIL 现场快速回收使用。

Standard equipment:

Oil-free compressors 17.2NM<sup>3</sup>/hX2 无油回收机 17.2 NM<sup>3</sup>/h 2 台

Suction pump 15NM<sup>3</sup>/h final vacuum 1mbar 回收终压 1mbar

Vacuum pump 160M<sup>3</sup>/h Roots pump 500 M<sup>3</sup>/h final vacuum 0.05mbar

5 m long DN20 rubber hose with couplings

Computer screen operation

Filter unit

Liquid storage



2100x1400x2180

1400kg

---

◆ Bottle scales HW250 SF6 钢瓶称重器

Bottle scales use for storage into SF6 bottle and other case。

Peeling fuction, net weight。

Weighing range 0-250kg 称重范围



◆ Multiple channel distributor 多路适配器

1、HD40/20F-3 , one side DN40 and one side DN20 for into, three side DN20 for out, and it has tree valve for each out side。

2、HD40/20F-6 one side DN40 and one side DN20 for into, six side DN20 for out, and it has six valve for each out side。。

