

◆ HC-393-002 SF6 Filling Device 充气装置 (全铜)

Portable aluminium case with 5 meters long rubber hose

标配 5 米长 DN8 管道 (包含便携式铝合金箱)

Coupling DN8 and DN20 标配 DN8/DN20 自封阀

Input 0-25Mpa 入口压力 0-25Mpa

Output -0.1-0.9Mpa 出口压力-0.1~0.9Mpa



◆ HCs-393-01 SF6 Filling Device 充气装置 (不锈钢)

Portable aluminium case with 5 meters long rubber hose

标配 5 米长 DN8 管道 (包含便携式铝合金箱)

Coupling DN8 and DN20 标配 DN8/DN20 自封阀

Input 0-25Mpa 入口压力 0-25Mpa

Output -0.1-0.9Mpa 出口压力-0.1~0.9Mpa Portable



◆ Bottle connection select 以上两款均可配

Serial	Type 可配钢瓶接头	Standard	Remarks
1	HDG/W 21.8x1/14"	EUR 欧标	
2	HDG-5/8n-W 21.8x1/14" P	China 国标	
3	HDG8/24.2-14YZ-MB-P	USA 美标	
4	Other special	According to sample and drawings	

◆ Customer' s coupling Option 可选配组合阀门

Order No: HZJ-15

You can select ABB、SIEMENS、GE

or provide drawing of customer .

配置目前市场比较流行的各个厂家的开关适用接口



◆ HCC-01-001 SF6-gas Filling Device 充气车

Mobile as cylinder cart with 6m long rubber hoses

And coupling DN7 DN8 DN12 with on module

可携带钢瓶运输，流动充气。

标配 6 米长 DN8 充气管，多种接口可选。

Standard equipment:

SF6 bottle connection

6 meters long DN8 wire-braided hose

SF6 pressure reducer

Input 0-25Mpa

Output -0.1-0.9Mpa

Please note the Bottle connection 购买前请标准钢瓶标准!



400X570X1360

30kg

◆ HCC-01-023/006 SF6 Filling Device With Bottle Weighing & Heating

◆ 带钢瓶称重和加热的充气车

Mobile as cylinder cart with rubber hoses

And coupling DN7 DN8 DN12 with on module

Weighing range 0-250kg (限重 0-250kg)

◆ Option

SF6 Bottle heating blanket 钢瓶加热毯

Power AC 110V /240V 1000W

Please note the Bottle connection 购买前请标准钢瓶标准!



◆ HVC-304-002 SF6 Evacuating and Filling Device 带抽真空的充气车

For evacuation of air and filling of SF6

14 m³/h vacuum pump final vacuum < 1mbar

Standard equipment:

SF6 bottle connection

6 meters long DN8 wire-braided hose 6米长铠装管 2根

SF6 pressure reducer

Vacuum pump(14m³/h) 14立方国产真空泵 极限真空小于1mbar

coupling DN8 & DN20



◆ HVC-304-002 SF6 Evacuating and Filling Device 带抽真空的充气车

mobile as cylinder cart with 6 meters long wire-braided hose

14 m³/h vacuum pump final vacuum < 1mbar

Control of solenoid valve. Can keep the pressure and Judge the leakage.

该产品可以有电磁阀控制，可真空保压判断开关柜是否泄漏。

Standard equipment:

SF6 bottle connection

6m DN8 wire-braided hose 6米长铠装管道一根

SF6 pressure reducer

Vacuum pump(14m³/h) 14立方国产真空泵 极限真空小于1mbar

coupling DN8 & DN20 接口可选配

Bottle connection select same to HVC-304-002



◆Couplings

HK7-08-022 P

&

HK7-08-022 P

for Alstom and GE GIS

HK12-08-022 P

HK12-08-022 P

DN7/DN12 快插接头
(GE、阿尔斯通用)



HC12-36-30n P

for GE GIS (NEW) and Schneider WSG

GE 用铜制 施耐德用铝制



HF8-20-26n T/P (DN8 自封阀)

HF20-36-45n P (DN20 自封阀)



HF40-56-76n T/STL (DN40 自封阀)

ABB LTB1145DI/8



◆ Three-Way Online Test

One Connect GIS , one Connect sensor, one side filling ---3 通测试阀



Moisture sensor